

FACT SHEET

1092/650 Easy Dome II

- Designed for a quick installation
- ¼" Sony Ex view HAD CCD 440.000 pixel – Sensitivity 0.01 Lux
- 480TVL horizontal resolution
- 26X optical zoom – 12X digital (312X total zoom)
- PAL, VBS: 1.0Vp-p , 75 ohm video output
- F1.6 – F3.8; focal length f:3.5 ~ 91 mm
- 360° horizontal rotation with 240 degree/sec maximum rotation speed
- 5 ~ 92° vertical rotation with 160 degree/sec maximum rotation speed
- 8 privacy zones
- S/N ratio 50dB
- 256 presets (235 can be used for camera "quick shooting")
- Preset auto patrol sequences: 30
- English OSD
- Auto-flip for +180° vertical rotation
- Proportional zoom
- **Auto tracking function built-in**
- 4In/2Out alarm
- RS486 for data exchange (protocols supported: PELCO-P, PELCO-D)
- 24Vac ±10%, 50Hz power supply
- Weight 1750 g
- Operating temperature (without heater) 0 ÷ +50°C
- Operating temperature (with heater) -25 ÷ +70°C
- AES, BLC, AGC
- Easy Dome I compatible

Accessories for the 1092/650

<p>1092/651 Kit includes:</p> <ul style="list-style-type: none"> • Wall bracket • Housing with fan & thermostate • Smoked Dome • Power supply 	<p>1092/652 Kit includes:</p> <ul style="list-style-type: none"> • Wall bracket & connection box • Housing with fan & thermostate • Smoked Dome • Power supply 	<p>1092/653 Kit includes:</p> <ul style="list-style-type: none"> • False-ceiling mount housing • Smoked Dome • Power supply
<p>1092/654 Kit includes:</p> <ul style="list-style-type: none"> • Ceiling surface mount (base and body) • Smoked Dome • Power supply 	<p>1092/655</p> <ul style="list-style-type: none"> • Corner installation Easy Dome II adaptor. This accessory can be used with 1092/652 bracket only 	<p>1092/656</p> <ul style="list-style-type: none"> • Pole installation Easy Dome II adaptor. This accessory can be used with 1092/652 bracket only
<p>1092/657</p> <ul style="list-style-type: none"> • Vandal cover KIT for 1092/651 and 1092/652 	<p>1092/690 General features:</p> <ul style="list-style-type: none"> • 3 Axis joystick (PTZ control) • English OSD • RS-485 and RS-422 • 230Vac 	<p>1092/691 General features:</p> <ul style="list-style-type: none"> • 3 Axis joystick (PTZ control) • English OSD • 8 video input (1Vp-p, 75 ohm) • 2 video output (1Vp-p, 75ohm) • RS-485 and RS-422 • 230Vac